

	VLT%	Film Color	Solar Energy			Visible Light		
			Transmittance	Absortance	Reflectance	Transmittance	Ext. Reflectance	Int. Reflectance
Bronze	20	Bronze	10.10%	28.50%	61.40%	20.90%	45.50%	46.60%
	35	Bronze	20.30%	30.10%	49.60%	35.90%	31.10%	32.90%
Silver	15	Silver	17%	35.90%	47.10%	23.60%	48.80%	47.90%
	35	Silver	27.30%	35.60%	37.10%	37.20%	35.50%	34%
Automotive	5	Black	-	-	-	6%	6%	-
	20	Black	-	-	-	21%	6%	-
	35	Black	-	-	-	35%	6%	-
	50	Black	-	-	-	51%	6%	-

	VLT%	Film Color	Winter U-Value	Summer U-Value	Shading Coefficient	Heat Gain Coefficient	Total Solar Energy Rejected	% IR Rejected	% UV Rejected
Bronze	20	Bronze	1.02	0.98	0.2	0.17	83%	95%	99%
	35	Bronze	1.02	0.99	0.32	0.28	72%	80%	99%
Silver	15	Silver	1.05	1.03	0.31	0.26	74%	89%	99%
	35	Silver	1.06	1.04	0.43	0.37	63%	70%	99%
Automotive	5	Black	-	-	-	-	40%	-	99%
	20	Black	-	-	-	-	36%	-	99%
	35	Black	-	-	-	-	35%	-	99%
	50	Black	-	-	-	-	28%	-	99%